



## FB30~FB35 FOUR WHEELS FORKLIFT SPECIFICATION

Specification	1	Model		FB30	FB35	
	2	Power type		electric	electric	
	3	Rated Capacity		kg	3000	3500
	4	Load Centre		mm	500	500
	5	Lifting Height		mm	3000	3000
	6	Fork Size	L×W×T	mm	1070×125×45	1070×125×50
	7	Tilting Angle	F/R (α°/β°)	Deg	6/12	6/12
Dimensions	8	Overall Dimension	Length (to fork face)	mm	2560	2560
	9		Overall Width	mm	1230	1230
	10		Mast Lowered Height	mm	2120	2120
	11		Mast Extended Height (with backrest)	mm	4160	4160
	12		Overhead Guard Height	mm	2250	2250
	13	Turning Radius	outside	mm	2315	2315
	14	Turning Radius	Min. insecting aisle	mm	2425	2425
	15	Front Overhang		mm	480	480
	16	Tread	(Front/Rear)	mm	1000/980	1000/980
	17	Ground Clearance	Min.	mm	120	120
	18	Wheelbase		mm	1710	1710
19	Fork Spread	Min./Max.	mm	250/1100	250/1100	
Performance	20	Speed	Travel (Laden)	km/h	15	15
	21		Lifting (Laden)	mm/s	300	280
	22	Max.Gradeability	Laden	%	15	15
	23	Service Weight (include battery )		kg	5100	5350
	24	Tire	Front		28*9-15-12PR	28*9-15-12PR
25	Rear			18*7-8-14PR	18*7-8-14PR	
Driven	26	Motor	Driven Motor	kw	15	15
	27		Lift Motor	kw	12	12
	28	Battery	Standard	V/Ah	80/500	80/550
	29	Controller	Manufacturer		CURTIS	CURTIS
	30	Operating Pressure for Attachment		Mpa	17.5	17.5