



## FB15~FB18 FOUR WHEELS FORKLIFT SPECIFICATION

Specification	1	Model		FB10	FB15	FB18	
	2	Power type		electric	electric	electric	
	3	Rated Capacity		kg	1000	1500	1800
	4	Load Centre		mm	500	500	500
	5	Lifting Height		mm	3000	3000	3000
	6	Fork Size	L×W×T	mm	920×120×35	920×120×35	920×120×35
	7	Tilting Angle	F/R ( $\alpha^\circ/\beta^\circ$ )	De g	6/12	6/12	6/12
Dimensions	8	Overall Dimension	Length (to fork face)	mm	2150	2150	2150
	9		Overall Width	mm	1090	1090	1090
	10		Mast Lowered Height	mm	1995	1995	1995
	11		Mast Extended Height (with backrest)	mm	3945	3945	3945
	12		Overhead Guard Height	mm	2170	2170	2170
	13	Turning Radius	outside	mm	1950	1950	1950
	14	Turning Radius	Min. insecting aisle	mm	2050	2050	2050
	15	Front Overhang		mm	420	420	420
	16	Tread	(Front/Rear)	mm	890/920	890/920	890/920
	17	Ground Clearance	Min.	mm	115	115	115
	18	Wheelbase		mm	1380	1380	1380
	Performance	19	Fork Spread	Min./Max.	mm	240/970	240/970
20		Speed	Travel (Laden)	km/h	15	15	15
21			Lifting (Laden)	mm/s	310	280	250
22		Max.Gradeability	Laden	%	15	15	15
23		Service Weight (include battery )		kg	2920	3070	3220
Driven	24	Tire	Front		6.50-10-10PR	6.50-10-10PR	6.50-10-10PR
	25		Rear		5.00-8-10PR	5.00-8-10PR	5.00-8-10PR
Driven	26	Motor	Driven Motor	kw	8	8	8
	27		Lift Motor	kw	8.6	8.6	8.6
	28	Battery	Standard	V/ Ah	48/400	48/440	48/495
	29	Controller	Manufacturer		CURTIS AC	CURTIS AC	CURTIS AC
	30	Operating Pressure for Attachment		Mp a	14.5	14.5	14.5

