

# ELECTRIC PALLET TRUCK CBD15G

## Advantages

- Fork fit for reversible pallets.
- Separately excited motor, strong climbing ability.
- Stepless speed control system, easy to operate.
- Battery open design, easy to replacement.
- Built-in charger.
- Sealed batteries free of maintenance, safe operation and no pollution.
- Small body, suitable for narrow space.
- Automatic lifting limit, safety, energy saving.
- Emergency reversing device and emergency brake switch.
- Low noise, low energy consumption, every day only 2kWh.



Built-in charger

Free-maintained battery

Fork suitable for reversible pallet

## CBD15G Electric Pallet Specification

1	Model	CBD15G		
2	Operating Type		Walkie	
3	Power Type		Electric	
4	Rated Capacity	kg	1500	
5	Load Centre	mm	600	
6	Wheels Type		PU	
7	Wheel Base	mm	1301	
8	Wheel Quantity-D/B/F		1/0/4	
9	Driving Wheel Size	mm	Φ252×67	
10	Bearing Wheel Size	mm	Φ84×70 (Double wheels)	
11	Balance Wheel Size	mm	/	
12	Min.fork Lowered Height	mm	85	
13	Max.fork Lifting Height	mm	205	
14	Max.lifting Height	mm	120	
15	Overall Fork Width	mm	550/685	
16	Inside Width between Forks	mm	230/365	
17	Fork Length	mm	1150/1200	
18	Fork Width	mm	160	
19	Fork Thickness	mm	75	
20	Overall Length	mm	1707	
21	Overall Width	mm	697	
22	Overall Height(With handle)	mm	1181	
23	Overall Height(Without handle)	mm	714	
24	Min.Turning Radius	mm	1547	
25	Min.Aisle Width for Pallets 800×1200	mm	1920	
26	Min.Aisle Width for Pallets 1000×120	mm	1953	
27	Speed	Travel (Laden/unladen)	km/h	3/3.5
28		Lifting (Laden/unladen)	mm/s	56/60
29		Lowering (Laden/unladen)	mm/s	57/59
30	Max.Gradeability	(Laden/unladen)	%	5/7
31	Service Weight (include battery)	kg	245	
32	Motor	Driven Motor	kw	DC 0.63
33		Lift Motor	kw	DC 0.8
34		Steering motor	kw	/
35	Battery	Volage/capacity	V/Ah	24/85
36		Weight	kg	52
37	Controller	Manufacturer		CARRY UP(Optional CURTIS)
38	Brake			Electromagnetic/Regenerative

