

ELECTRIC STACKER

CDD15K/CDD20K
CTD15K/CTD20K

2 YEARS WARRANTY



SPECIFICATION

1		Model	CDD15K/CDD20K		
General	2	Operating Type	Stand on		
	3	Power Type	kg	Electric	
	4	Load Capacity	c(mm)	1500/2000	
	5	Load Center		600	
Characteristic & Dimension	6	Wheel Type	y(mm)	Polyurethane	
	7	Wheelbase	mm	1355	
	8	Wheel Size,front	mm	Φ250×75	
	9	Wheel Size,rear	mm	Φ80×70	
	10	Additional wheel	b11(mm)	Φ115×50	
	11	Thread,rear	h1(mm)	570/685	
	12	Lowered Mast Height	h3(mm)	2085/1765/2015/2165/ 2330/2000/2170/2340	
	13	Max.lifting Height	h4(mm)	1600/2500/3000/3300/ 3500/4500/5000/5500	
	14	Extended Mast Height	h13(mm)	2085/3050/3550/3850/ 3950/5050/5550/6050	
Performance	15	Lowered Fork Height	l1(mm)	90	
	16	Overall Length	b1(mm)	2010/2020	
	17	Overall Width	S/e/l(mm)	790	
Chassis	18	Fork Dimensions	b5(mm)	60/170/1150	
	19	Width over Forks	Ast(mm)	570/685	
	20	Aisle Width, with Pallet 1000x1200 Crosswise	Ast(mm)	2900	
	21	Aisle Width, with Pallet 800x1200 Lengthwise	m2(mm)	2840	
	22	Groud ClearanceFork width	mm	40	
Power & Transmission	23	Turning RadiusFork thickness	m/s	1600	
	24	Speed	Lifting (Laden/unladen)	m/s	/
	25		Falling(Laden/unladen)	%	hand control
	26	Max.Gradeability (Laden/unladen)	kg	8/10	
	27	Service Weight (include battery)		1050/1220/1185/1350	
	28	Service brake	kw	Electromagnetic / Regenerative	
	29	Motor	Driven Motor	kw	1.2/1.5
	30		Lift Motor		3.3
	31		Steering Motor Type	V/Ah	Electric
	32	Battery	Voltage/noinal Capacity	mm	24/110(240)
	33		Size(L×W×H)		650×197×530

